


Aluminium column SAL-8,5 Wł 1/2,5/3,2/5
diameter 176 mm at the base plate



Technical data

Aluminium Column		SAL-8,5 Wł 1/2,5/3,2/5
Product code		42416
Column height H [m]		8,5
Height of lower section h1 + E [m]		5,3 + 0,35
Lower wall thickness [mm]		4,3
Height of upper section h2 [m]		3,2
Upper wall thickness [mm]		4
Net weight [kg]		50,7
Volume [m³]		0,76
Post top column		luminaires with Ø60 spigot entry with weight and windage not exceeding data in resistance calculations
Concrete footing / reinforcement basket		B-70 / Z-70
Concrete footing code/reinforcement basket code		311170 / 311207
Hot galvanized nut set /Hot galvanized ripable nut set		4012 / 4013

Resistance calculations

SAL-8,5 Wł 1/2,5/3,2/5 code 42416	acceptable windage of single luminaire [m²] for Cx=0,7			
	Vref. = 22 m/s	Vref. = 24 m/s	Vref. = 26 m/s	Vref. = 28 m/s
acceptable mass of luminaires [kg]	I zone, III location category	I and III zone, III location category to 450m AMSL	II zone, III location category	III zone, III location category to 755m AMSL
15	0,60	0,48	0,33	0,28

- surface: polished aluminium
- anodizing in 12 colours
- option of powder painting in RAL colours (other colours available on request)
- elastomer protection option in the color of the column to a height of 350 mm (other height on request)
- ROSA standard wiring chamber
- packing: sleeve material

